

TAKE TK ANYWHERE

Lightweight, portable and with a choice of power options, using either the AC adapter provided, or with an optional 14.8V/26V battery, the TK-140B/280B gives you light where and when you want it - in the studio, on set or even in the most remote locations.



AC Adapter (Included)



14.8V V-mount Battery (Optional)



26V V-mount Battery (Optional)

2X14.8V | 1X26V | 2X26V

TK Technical Data

Model	TK-140B	TK-280B
Rated Power	160W	280W
Input Voltage/Current	DC24V/6.67A Max, AC100-240V 50/60Hz	DC48V/5.84A Max, AC100-240V 50/60Hz
Beam Angle	120°	
CRI	Average 95	
TLCI	Average 98	
CCT	2700K-7500K	
Dimming	0-100%	
Control	On-board controller, 2.4G, Bluetooth, DMX [Connection method: 5 Pin XLR cable], RDM, LumenRadio	
Effects	CCT Loop, INT Loop, Flash, Pulse, Storm Auto, Storm Manual, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion Auto, Explosion	
Housing	Aluminium	
Mounting	Yoke, Central Mount	
Cooling	Passive air cooling	
Product Size	Light fixture (with yoke): 890x85x540mm/35.04x3.35x21.26"	Light fixture (with yoke): 1340x85x540mm/52.76x3.35x21.26"
Product Weight	Light fixture+Yoke+Barndoor: 8.52kg/18.78lb	Light fixture+Yoke+Barndoor: 18.78kg/30.33lb
Includes	TK-140Bx1 Barndoorx1 Power Adapterx1 Power Cablex1 Yokex1 User Manualx1 DMX Reference Guidex1	TK-280Bx1 Barndoorx1 Power Adapterx1 Power Cablex1 Yokex1 User Manualx1 DMX Reference Guidex1
Optional Accessories	Eggcrate, Honeycomb Grid, Portable Soft Bag, Central Mount, Flight Case	

Illumination (lux / fc)

Model	TK-140B				TK-280B			
	1M	3M	5M	7M	1M	3M	5M	7M
3200K	3506 lux 326 fc	407 lux 38 fc	168 lux 16 fc	93 lux 9 fc	5572 lux 518 fc	809 lux 75 fc	333 lux 31 fc	185 lux 17 fc
5600K	3757 lux 349 fc	428 lux 40 fc	175 lux 16 fc	97 lux 9 fc	5900 lux 548 fc	860 lux 80 fc	353 lux 33 fc	195 lux 18 fc