

MULTIPLE CONTROL OPTIO


Making sure you stay fully in control at all times, the TK Series supports on-board control, DMX wi options via built-in Bluetooth, 2.4G, Lumenradio :



On-Board
Controller



DMX



Bluetooth



2.4Ghz WiFi



Lumenradio
TIMO RX

BRIGHTER AND STRONGER

TK-200/450 is an exceptional high power and con Power reach up to 240W and 455W and able to pro requirements in the large scene.

TK Technical Data	
Model	TK-200
Rated Power	240W

Input Voltage/Current	DC24V/10.4A Max, AC100-240V
Beam Angle	120°
CRI	96
TLCI	98
CCT	5600K
Dimming	0-100%
Control	On-board control, 2.4G, Bluetooth
Effects	INT Loop, Flash, Pulse, Storm, Explosion manual, Welding
Housing	Aluminium
Mounting	Yoke, Central Mount
Cooling	Passive air cooling
Product Size	Light fixture (with yoke): 890×85×540mm/35.04×3.35×21
Product Weight	Light fixture+Yoke+Barndoor: 8.14kg/17.95lb
Includes	TK-200×1 Barndoor×1 Power Adapter×1 Power Cable×1 Yoke×1 User Manual×1 DMX Reference Guide×1
Optional Accessories	Eggcrate, Honeycomb Grid, Poi

Model	<i>TK-200</i>		
Distance	1M	3M	
5600K	6888 lux 640 fc	901 lux 84 fc	

www.nanlux.com